

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9511010
Type of light source: LED



Product information Sheet

General Information

Material number	9511010
Type	Pendant light
Product segment	INDOOR

Dimensions

Diameter (in cm)	12 Cm
Width (in cm)	
Height (in cm)	120 Cm
Net Weight	

Material & Colour

Enclosure Material	Iron & alu & optics acrylic
Colour	Gold
Adjustable	

Functionality

Switch Type	
Function	
Battery	
USB Charger	

Technical Information


Protection Degree	IP20
Protection Class	I
Mains Voltage	220-240V
max. Wattage	5.59W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	91,6
Rated Lamp Power (0,1W precision)	5.59W
Colour Tolerance (LED, SDCM)	3,4

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tunable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	5.59
Energy efficiency class	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	246,73
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	5.59W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	91,6
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	A:D37*2.0 2835/0.5W/14pcs/3W B:D17*1.5 6pcs/1.2W"
Spectral power distribution in the range 250 nm to 800 nm, at full-load	



Parameters for LED and OLED light sources

R9 colour rendering index value	74
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ($\cos \phi_1$)	0,712
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources	0,712
Colour consistency in MacAdam ellipses	3,4
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	3,4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	0,177
Flicker metric (PstLM) for LED and OLED light sources	0,177
Stroboscopic effect metric (SVM) [X,X]	0,05
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,05
P_{on} in W	5.59W
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	

