

# NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9533521

Type of light source: LED



## Product information Sheet

### General Information

Material number	9533521
Type	Wall Lamp
Product segment	INDOOR

### Dimensions

length (in cm)	35 Cm
Width (in cm)	10 Cm
Height (in cm)	8 Cm
Net Weight	0.6 kg

### Material & Colour

Enclosure Material	Metal
Colour	Sandy Black

### Functionality

Switch Type	knife switch
Function	lighting
Battery	No
USB Charger	Yes

### Technical Information

Protection Degree	IP20
Protection Class	I
Mains Voltage	230V
max. Wattage	Backlight 5W & Reader 3W
Lumen	350 & 210 Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000h
Switching Cycles	on-off
Colour Rendering Index (Ra, CRI)	CRI: 83,4
Rated Lamp Power (0,1W precision)	8W
Colour Tolerance (LED, SDCM)	±100K

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	3
Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	230 in sphere
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power ( $P_{on}$ ), expressed in W [x,x]	3W
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0.00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre): Height: Width: Depth:	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	[graphic]
Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	x=0.374, y=0.362

## Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	

## Parameters for LED and OLED light sources

R9 colour rendering index value [x]	23
Survival factor [x,xx]	1.00
The lumen maintenance factor [x,xx]	0,96
Displacement factor ( $\cos \phi_1$ )	
Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	
Stroboscopic effect metric (SVM) [X,X]	
Pon in W	2,65
Stanby Power (Psb) in W	0
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	3,3

